




HabasitLINK® IS610-R (Radius Flush Grid)



Description

- 1 inch pitch
- Belt turning radius equals 2.2 times the nominal belt width up to 24 inches (609.6 mm)
- Belt turning radius equals 2.5 times the nominal belt width over 24 inches (609.6 mm)
- 46% open area; 77% open contact area; largest opening 7.3x9.5 mm (0.29"x0.37")
- Food approved materials
- Bi-directional
- Connecting rod diameter = 0.156 inch (4.0 mm)
- Standard belt width increments = 3 inch (76.2 mm) nominal, starting from 6 inches (152.4 mm)
- Non-standard widths available in 1/2 inch (12.7 mm) increments starting at 3 inches (76.2 mm) upon request
- Material selection may affect belt width — please contact your local partner for actual dimensions




Belt data

Belt material		PA	POM	PP
Rod material		PA		
Nominal tensile strength F'_N straight run	N/m	15328	15328	10219
	lb/ft	1050	1050	700
Nominal tensile strength F_N in curve ⁽¹⁾	N	1334	1334	800
	lbf	300	300	180
Temperature range	°C	-40 - 118	-40 - 93	5 - 105
	°F	-40 - 245	-40 - 200	40 - 220
Belt weight m_B	kg/m ²	4.4	6.4	3.4
	lb/sqft	0.91	1.03	0.70
Standard belt color		dark gray	blue/off-white	gray/white

Belts are available in PP/PP+GR (PP rods) and PE (PE rods) materials for straight applications. Additional belt colors and materials available.

Belt accessories



Hold-down tabs

Inserts

Note: Inserts may affect belt pull

Rollers

Note: The use of rollers will change the turning radius to 3.5

Standard flights

Standard flights are available in 1" and 2" heights. Standard flight indent is 1" or 3" from outside edge of belt

Side guards

Side guards are available in standard 1" and 2" heights. Note: Side guards must be indented a minimum of 1" from outside edge of belt

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.