Habasit – Solutions in motion



Fabric Processing Belt



More Than Just a Food Belt

Habasit's FNB-12E, originally developed for food processing, has found many uses in other industries as well. This TPU-coated, fabric belt has been primarily used for conveying and processing baked snacks, bread, confections, convenience food, pastry, pasta, and pizza. However, it's also hard at work in other industrial operations including:

- Wood finishing
- Laminating
- Packaging
- Die cutting
- Metal stamping
- Transfers of mfrd. products


This tough belt resists cuts, abrasion, oils, and a broad range of chemicals. It's dense, void-free, TPU coatings, and nonadhesive surface supports thorough cleaning. FNB-12E operates reliably within temperatures ranging from 5 - 176° F (-15 – 80° C). Available in seamless widths up to 157.48" (4000mm) to meet the need of wide operations without longitudinal seaming.


Key Benefits:

- Non-adhesive, low friction surface with good release properties
- High strength, low stretch for heavy loads, short take-up
- Anti-static
- FDA approved
- Laterally rigid, longitudinally flexible for short transfers
- Resists cuts, impacts, abrasions, and oils

FNB-12E Technical Details







Key Features	
Conveying Side Material & Properties	Thermoplastic polyurethane (TPU), Matt, Non-adhesive
Pulley Side Material & Properties	Polyester (PET), Impregnated fabric, Non-adhesive
Traction Layer Material	Polyester (PET)
Conveying Side Color	White
Pulley Side Color	Light gray
Number of Fabrics	2
Anti-statically equipped	Yes
Adhesive-free joining method	Yes
Slider bed suitable	Yes
Carrying rollers suitable	Yes

Technical Data				
Thickness of belt	2.4	mm	0.09	inch
Tensile force 1% elongation after relaxation (k 1% relaxed) per unit of width (Habasit Standard SOP#-155 / EN ISO 21181)	12	N/mm	69	lbf/in
Min. operating temperature admissable (continuous)	-15°	С	5°	F
Max. operating temperature admissable (continuous)	80°	С	176°	F
Pulley diameter (minimum)	50	mm	1.97	inch
Pulley diameter minimum with counter flection	60	mm	2.36	inch
Seamless manufacturing width	4000	mm	157.48	inch

See www.habasitamerica.com for full product data sheet.

Contact your local Habasit representative to discuss availability and additional capabilities needed to meet customer requirements.

Information provided herein does not constitute legal representations or warranties and may change without notice. Please refer to the specifications disclaimers provided in the respective product data sheets.

For further information choose country selection Habasit Worldwide on:

dwide on: Suwanee, GA 3002 Phone: 800.458.64 Fax: 678.288.3654

www.habasitamerica.com

Habasit America 805 Satellite Blvd Suwanee, GA 30024 Phone: 800.458.6431

E-mail: info.america@us.habasit.com

Copyright Habasit AG Subject to alterations

Printed in 4521FLY.CVB-en0721USA